



MEMBER OF
BIMCO
SINCE 1999

LIDER KEREM -VESSEL PARTICULARS-

FLAG	REPUBLIC OF TURKIYE
CALL SIGN	TCA8677
PORT OF REGISTRY	ISTANBUL
IMO NUMBER	9394076

OWNER	LİDER GEMİ SANAYİ TURİZM NAKLİYAT VE TİCARET LİMİTED ŞİRKETİ ADRES: DEREBOYU SK. ÇARŞI MAH. DAİRE NO:1 KAPI NO:18 ORTAHİSAR - TRABZON / TÜRKİYE			OPERATOR	COSHIP DANISMANLIK HİZMETLERİ VE TURİZM LTD. STİ. GAYRETTEPE MAH. HOSSOHBET SK. NO:18/4 CELİK APT. C1 BLOK, BESİKTAS – İSTANBUL / TÜRKİYE		
COMPANY IMO NO	5170723			OPR. IMO NO	6153820		
PH	+90 216 392 8399			PH	+90 212 216 1088		
E-MAIL	operation@lidergemi.net			E-MAIL	tanker@coship.net		
CLASSIFICATION	RINA – CLASS NUMBER: 103699						
CLASS.NOTATION	RINA – C HULL • MACH OIL TANKER ESP – CSR – DOUBLE HULL ; CHEMICAL TANKER ESP – DOUBLE HULL – IMO 3 UNRESTRICTED NAVIGATION / AUT – UMS / INWATERSURVEY						
P & I / H & M	P&I : THE AMERICAN CLUB / H&M: INTEGRA						
BUILT	KEEL LAID	29 December 2005		BUILDING CONTRACT	22 November 2022		
	DELIVERY	02 September 2025		-			
SHIPYARD & HULL NO	SHIPYARD: DENTAS GEMİ İNSAAT VE ONARIM SANAYİİ A.S – TUZLA TÜRKİYE / HULL NO: NB 262						
MMSI NUMBER	271053573						
GSM PHONE	+90 544 371 4503						
E-MAIL	liderkerem@coship.net						
INMARSAT C	427103037 / 427103036			INM C e-mail	427103036@inmc.eik.com		
LOA	149.35	mtrs	DIST. FROM BRIDGE FRONT TO BOW		126.60	mtrs	
LBP	143.15	mtrs	DIST. FROM BRIDGE FRONT TO STERN		22.75	mtrs	
BREADTH MOULDED	17.3	mtrs	DIST. FM BRIDGE FRONT TO MANIFOLD		51.20	mtrs	
DEPTH MOULDED	10.1	mtrs	DIST. FM BOW TO AFT MANIFOLD		108.10	mtrs	
HIGHT OF MAST WITH ANTENNA	29.1	mtrs	DIST. FM STERN TO AFT MANIFOLD		41.25	mtrs	
DIST. FROM BOW TO MID MANIFOLD	75.40	mtrs	DIST. FM BRI. FRONT TO AFT MANIFOLD		18.50	mtrs	
DIST. FROM STERN TO MID MANIFOLD	73.95	mtrs	-		-		
TONNAGE	INTERNATIONAL		SULINA	SUEZ	-		
GRT	7285		7543.02	-	-		
NRT	3997		5779.73	-	-		
DEADWEIGHT DRAFT FREEBOARDS	DISPLACEMENT (t)		DEADWEIGHT (t)	DRAFT (EXT) (m)	FREEBOARD (m)		
FW	16856		13710	7.614	2.498		
SUMMER	16891		13330	7.459	2.653		
WINTER	16511		12950	7.304	2.808		
BALLAST	8730		5169	4.067	6.045		
FRESH WATER ALLOWANCE	173		mm	AIR DRAFT	LOAD/BALLAST/LIGHT		
LIGHT SHIP	3561		Ton	COLLAPSED MAST	14.28 / 17.54 / 19.99		
TPC	24.52		t/cm	RAISED MAST	21.64 / 24.90 / 27.35		
CAPACITY OF CARGO TANKS	12 COT + SLOP P/S		12 COT + SLOP P/S	12 COT	SLOP P/S		
CARGO TANKS COATED W. PURE EPOXY PAINT	14,459.830 m³ (100%)		14,170.633 m³ (98%)	14,210.655 m³ (100%)	249.175 m³ (100%)		
BALLAST CAPACITY	14 WBT - 5092 m³ (100%)			SVANEHOJ DEEPWELL, CENTRIFUGAL			
BALLAST TANKS COATED W. EPOXY PAINT				45 KW 2x400 m³/h			
CARGO PUMPS	SVANEHOJ DEEPWELL, CENTRIFUGAL			SVANEHOJ DEEPWELL, CENTRIFUGAL			
	94 KW – COTs 12x250 m³/h			42 KW – SLOPs 2x100 m³/h			
CAPACITY OF DIESEL OIL TANKS	263.800 m³ (100%)		226.868 MT (SG0.86)	250.61 m³ (95%)	215.524 MT (SG0.86)		
CAPACITY OF FRESH WATER TANKS	268.940 m³ (100%)		-	-	-		
MAIN ENGINE & AUXILARY	ME – WARTSILLA W6L32B3 2760 KW AE - 2x MAN D2840LE301 443 KW			AE - 1x SCANIA DI13 M 376 KW EMG DG - 1x MAN-D2866E 110 KW			
PROPULSION	1 PITCH PROPELLER (CPP), 750 RPM - RIGHT HANDED						
BOW THRUSTER	1x250 KW THRUSTER	THRU. IMMERSION	FP 1.80 m	(105%)	FP 1.86 m	(110%)	
PROPELLER IMMERSION	AP 3.66 m	(105%)	AP 3.82 m	(110%)	-		
ANCHOR (HHP) & CHAIN (46 mm Q3)	PORT ANCHOR CHAIN		9 SHACKLES @ 27.5 m				
WEIGHT OF ANCHORS (2665 Kg)	STB ANCHOR CHAIN		9 SHACKLES @ 27.5 m				